



**Note:**  
Middle section must be extended at least two rungs before the ladder is fully extended.

## 4061 Rope-operated extension ladder, three-section

- › Inner width of the ladder 300 mm (upper section).
- › Rolled profile rungs.
- › Ladder feet pressed into the stile.
- › Maximum grip ropes in different colours to distinguish:  
upper section: Ø 10 mm, colour orange; middle section: Ø 10 mm, colour blue.
- › With high-quality plastic wall rollers.
- › Guide fittings made of solid steel.



Number of rungs		3×12	3×14	3×16
Stile	approx. mm	83/89	89	89/100
Number of rungs	at max. extension	29	34	40
Length	retracted approx. m	3.57	4.13	4.69
Length	extended approx. m	8.33	9.76	11.44
Standing height	approx. m	7.02	8.37	10.00
Working height	approx. m	8.52	9.87	11.50
Reach height	approx. m	9.02	10.37	12.00
Width	extended top/middle/bottom approx. mm	355/425/490	355/425/490	355/425/490
Weight	approx. kg	28.5	33.0	39.0
EAN-Code		4019502339323	4019502339330	4019502339347
Order no.		406136	406142	406148

For an explanation of working/standing/reach height see on page 5.

### Recommended accessories:



P. 176  
Cross-beam for ladder section



P. 174  
Set of foot pikes for stiles



P. 178  
Telescopic wall spacer for rung ladders



P. 178  
Ladder holder set for gutters



P. 182  
Ladder bracket set for roof racks