



## 6011 Rung leaning ladder

- › Inner width of the ladder 370 mm.
- › Stiles of seamless extruded profiles with ergonomic shape.
- › Rungs made of extruded profiles with deep ribbing, and therefore increased slip resistance.
- › Ladder feet screwed to the stile (easily replaceable).
- › Stable stiffening braces on first step.



Number of rungs		6	7	8	9	10	12	14	16	18	20	22
Stile	approx. mm	60	60	60	60	60	60	60	66	71	71	71
Length	approx. m	1.88	2.16	2.44	2.72	3.00	3.56	4.12	4.68	5.24	5.80	6.36
Standing height	approx. m	0.82	1.09	1.36	1.63	1.90	2.44	2.98	3.52	4.06	4.60	5.14
Working height	approx. m	2.32	2.59	2.86	3.13	3.40	3.94	4.48	5.02	5.56	6.10	6.64
Reach height	approx. m	2.82	3.09	3.36	3.63	3.90	4.44	4.98	5.52	6.06	6.60	7.14
Width	approx. mm	425	425	425	425	425	425	425	425	425	425	425
Weight	approx. kg	3.3	3.8	4.2	4.6	5.2	6.3	7.3	8.0	10.0	11.2	12.5
EAN-Code		4019502338234	4019502338241	4019502338258	4019502338265	4019502338272	4019502338296	4019502338302	4019502338319	4019502338326	4019502338333	4019502338340
Order no.		601106	601107	601108	601109	601110	601112	601114	601116	601118	601120	601122

For an explanation of working/standing/reach height see on page 5.

### Recommended accessories:



P. 176

Cross-beam for ladder section



P. 177

Suspension hook set



P. 177

Suspension set