

ESCALERAS ESTÁNDAR DE FIBRA

ESCALERA DE FIBRA TRANSFORMABLE DE 2 TRAMOS

Permite su uso como escalera de tijera y extensible.

Opción de separar los tramos.



Norma
UNE-EN 131

Norma
UNE-EN 50528

Aislamiento
100 KV

Modelo	Nº peld.				Kg
FC6206	2x6	1780	3000	665	15
FC6207	2x7	2060	3560	705	16,5
FC6208	2x8	2340	4120	745	18
FC6209	2x9	2660	4680	795	19,5
FC7210	2x10	2940	4960	835	21
FC7211	2x11	3220	5520	880	22,5
FC7212	2x12	3500	6080	925	24



Mod. FC7210



ESCALERA DE FIBRA TRANSFORMABLE DE 3 TRAMOS

Permite su uso como escalera de tijera y extensible.

Opción de separar los tramos.



Norma
UNE-EN 131

Norma
UNE-EN 50528

Aislamiento
100 KV

Modelo	Nº peld.					Kg
FC7306	3x6	1885	2985	4115	726	25
FC7307	3x7	2165	3545	4955	775	27
FC7308	3x8	2445	4105	5795	824	29
FC7309	3x9	2725	4385	6075	873	31
FC7310	3x10	3005	4945	6915	922	33
FC7311	3x11	3285	5505	7755	971	35



Mod. FC7310

